



A fuel tester that makes a powerful difference in line and hangar maintenance

The PSD60-2R is an accurate, highly reliable, portable capacitance test set. Along with an aircraft specific interface, the PSD60-2R will test any AC Capacitive Fuel, Water, LOX, Engine Oil, or other AC capacitive system.

The PSD60-2R performs these functions:

- Measurement of total tank capacitance, individual tank units and compensators
- Simulation of capacitance for indicator calibration
- Simulation of compensator capacitance value for dry calibration
- Measurement of the insulation resistance of tank units and aircraft harness
- Measurement of coax center conductor to shield for fault isolation
- Display of capacitance resolution to 0.00 pF for accurate individual tank unit testing (in 199.99 pF range)

FEATURES

- Compatible with AD 98-20-40 & AD 99-03-04 compliant aircraft (Mod 6 and above)
- Modular design for high reliability and low maintenance
- Closed box calibration using front panel controls - performed annually
- Battery powered with percent of charge displayed
- Maintenance codes displayed to aid in troubleshooting
- Distance-to-Fault (DTF) Mode determines the “length” of the wire or the approximate distance to a break in the wire or shield
- Large selection of aircraft specific interface cables available



Aircraft Fuel Interfaces

SPECIFICATIONS

MEASUREMENT RANGE

Capacitance	
Low	0.00 to 199.99 pF (0.01 pF res.)
Mid	200.0 - 1999.9 pF (0.1 pF res.)
High	2,000 - 19,999 pF (1 pF res.)
	20.00 K - 39.99 K pF (10 pF res.)
DTF	0.00 to 19,999 pF (1 pF res.)
	20.00 K - 39.99 K pF (10 pF res.)
Resistance	10 mΩ to 1,999 MΩ in 9 ranges
	Optional range: 2,000 MΩ to 19,999 MΩ

MEASUREMENT ACCURACY

AC Capacitance	
Mode A	Greater of ± 0.1 % of reading or 0.05 pF from 0-39.99 K pF at 0 to 30 degrees Phase Shift
Mode B	Greater of ± 0.1 % of reading or 0.05 pF from 0-39.99 K pF at 0 to 359 degrees Phase Shift
DTF	Greater of ± 0.1 % of reading or 2 pF.
Resistance	Greater of 2% of reading or 0.1 ohm greater, from 0.00 Ω to 1,999 MΩ
	$\pm 5\%$ in optional range 9 (2,000 MΩ to 19,999 MΩ)

CAPACITANCE SIMULATOR RANGE

Tank Unit	10-9,900 pF infinite resolution
Compensator	10-990 pF with infinite resolution

PHYSICAL CHARACTERISTICS

Weight	12 lbs (5.4 kg)
Width	14 in (35.6 cm)
Height	6.5 in (16.5 cm)
Depth	10.6 in (26.9 cm)
Power	27 V, 150 mA maximum
Batteries	18 Alkaline C size non-rechargeable, internally mounted

ENVIRONMENTAL

Operating Temperature	-25 °C - +55 °C
Operating Altitude	≤ 2,000 m

VERSIONS, OPTIONS AND ACCESSORIES

When ordering, please include the order number listed below.

Order Number	Versions
693	PSD60-2R AC Universal Fuel Capacitance Test Set

Aircraft specific interface cables are required and must be purchased separately. Contact Cobham AvComm for your application.

Standard Accessories

58345	Cable GND Fuel Quantity (55-7002-00)
75322	Operations Manual and CD

Extended Warranty

84388	Extended standard warranty 36 months with scheduled calibration
84389	Extended standard warranty 60 months with scheduled calibration



For further information please contact:

Cobham AvComm
10200 West York Street
Wichita, KS 67215-8935 [USA]
Phone: (316) 522-4981
Fax: (316) 524-2623
AvComm.TechSales@cobham.com

or contact your Cobham AvComm sales office