

VIAVI

ATC-5000NG

NextGen ATC/DME Test Set and ADS-B Target Generator

Transmitter

Frequency	
Range	952 MHz to 1223 MHz
Resolution	100 KHz
Accuracy	2.5 ppm
Phase Noise	>80 dBc/Hz @ 100 KHz
Power	
Range (Transponder)	+5 to -110 dBm
Resolution	0.1 dB
Accuracy @ 1030 MHz	±1 dB [+5 to -100 dBm] ±3 dB [< -100 dBm]
Range (UAT)	+5 to -110 dBm
Resolution	0.1 dB
Accuracy	±1 dB @ 978 MHz
Range (DME)	+5 to -110 dBm
Resolution	0.1 dB
Accuracy	±1 dB [+1 to -100 dBm] ±3 dB [< -100 dBm] 952 to 1223 MHz

Spectral Purity	
Harmonics	>50 dBc
Spurious	>55 dBc, 350 to 1800 MHz
Residual FM	250 Hz Peak
Channels	
No. of Channels	4 (XPDR/UAT) 6 (ADS-B Option)
Diversity	
Power	±20 dB
Resolution	1 dB
Accuracy	±1 dB
Timing	±1 uS
Resolution	25 nS
Accuracy	±10 nS
Modulation	
Pulse On/Off Ratio	>80 dB
Pulse Position (high speed rise/fall time mode)	
Mode A Interrogation P1-P3 Default	8.0 uS
Accuracy	±10 nS
Mode C Interrogation P1-P3 Default	21.0 uS
Accuracy	±10 nS
ATCRBS Interrogation P1-P2 Default	2.0 uS
Accuracy	±10 nS
ATCRBS Interrogation P3-P4 Default	2.0 uS
Accuracy	±10 nS
ATCRBS Interrogation Variation	±1.95 uS
Resolution	25 nS
Accuracy	±10 nS



Transmitter (continued)

Pulse Position (high speed rise/fall time mode) - (continued)	
Mode S Interrogation P1-P2 Default	2.0 uS
Accuracy	±10 nS
Mode S Interrogation P1-P2 Variation	±1.0 uS
Resolution	25 nS
Accuracy	±10 nS
Mode S Interrogation P1 to P6 Default	3.5 uS
Accuracy	±10 nS
Mode S Interrogation P6 Variation	±1.95 uS
Resolution	25 nS
Accuracy	±10 nS
Mode S Interrogation P2 to SPR Default	2.75 uS
Accuracy	±10 nS
Mode S Interrogation SPR Variation	±1.0 uS
Resolution	25 nS
Accuracy	±10 nS
Mode S Interrogation P5 prior SPR Default	400 nS
Accuracy	±10 nS
Mode S Interrogation P5 Variation	±1.95 uS
Resolution	25 nS
Accuracy	±10 nS
Interference Interrogation Signal #1	-44 to 400 us
Resolution	25 nS
Accuracy	±10 nS
Interference Interrogation Signal #2	0 to 400 us
Resolution	25 nS
Accuracy	±10 nS
Double Interrogation	0 to 400 us
Resolution	25 nS
Accuracy	±10 nS
Pulse Width (high speed rise/fall time mode)	
ATCRBS Interrogation P1/P2/P3 Default	0.8 uS
Accuracy	±10 nS
ATCRBS Interrogation P4 Short	0.8 uS
Accuracy	±10 nS
ATCRBS Interrogation P4 Long	1.6 uS
Accuracy	±10 nS

ATCRBS Interrogation P1/P2/P3/P4 Variation	0 to 1.95 uS
Resolution	25 nS
Accuracy	±10 nS
Mode S Interrogation P1/P2 Default	0.8 uS
Accuracy	±10 nS
Mode S Interrogation P1/P2 Variation	0 to 1.95 uS
Resolution	25 nS
Accuracy	±10 nS
Mode S Interrogation P6 Short Default	16.25 uS
Accuracy	±10 nS
Mode S Interrogation P6 Long Default	30.25 uS
Accuracy	±10 nS
Mode S Interrogation P6 Variation	
P6 Overall	-0.5 to +1.45 uS (offset range)
P6 End	0 to 1.95 uS
Resolution	25 nS
Accuracy	±10 nS
Mode S Interrogation P5 Default	0.8 uS
Accuracy	±10 nS
Mode S Interrogation P5 Variation	0.2 to 1.95 uS
Resolution	25 nS
Accuracy	±10 nS
Interference Pulse Width	0.2 to 32.0 uS
Resolution	25 nS
Accuracy	±10 nS
Pulse Rise/Fall Time	
Transponder	<50 / <50 nS
Accuracy	<50 nS
Pulse Amplitude	
Video Data Block Variation	+3 to -4 dB
Resolution	1 dB
Accuracy	±1 dB
ATCRBS Interrogation Variation	+9 to -19 dB
Resolution	1 dB
Accuracy	±1 dB
Interference	+9 to -19 dB
Resolution	1 dB
Accuracy	±1 dB

Transmitter (continued)

Block Transmissions	
XPDR	2000 messages
No. of Blocks	1 to 50,000 or indefinite
Interrogation Rate within Block	User defines spacing between interrogations
Period	10 ms to 90 seconds
Resolution	1 ms
Accuracy	±1 ms
PRF	
ATCRBS Interrogations	1 to 10,000 Hz
Resolution	1 Hz
Accuracy	0.1% of setting
Mode S Interrogations	1 to 2500 Hz
Resolution	1 Hz
Accuracy	0.1% of setting
Double Interrogation	
Each message:	1 to 2500 Hz
PRF	in sync or non-sync
Resolution	1 Hz
Accuracy	0.1% of setting
Interlace	1 to 400 Hz
Resolution	1 Hz
Accuracy	0.1% of setting
Interlace Ratio	
Ratio	1:1 to 1:1000
DME Simulation	
Ident Frequency	1350 Hz
Accuracy	±0.02%
Dot Default	120 ms
Accuracy	±1 ms
Dot Variation	50 to 250 ms
Resolution	10 ms
Accuracy	±1 ms
Dash Default	360 ms
Accuracy	±1 ms
Dash Variation	150 to 750 ms
Resolution	10 ms
Accuracy	±1 ms
Space Default	150 ms
Accuracy	±1 ms
Space Variation	50 to 250 ms
Resolution	10 ms
Accuracy	±1 ms
Code Rate Default	37 s
Accuracy	±100 ms

Code Rate Variation	10 to 65 s
Resolution	0.1 s
Accuracy	±100 ms
Echo Power Variation	-15 to +6 dB
Resolution	0.1 dB
Accuracy	±0.25 dB
Echo Range	30 nmi
Accuracy	±0.02 nmi
Range	0 to 400 nmi
Resolution	0.01 nmi
Accuracy	±0.02 nmi
Velocity	0 to 10000 knots
Resolution	1 knot
Accuracy	±0.001%
Acceleration	0 to 400 ft/s ²
Resolution	1 ft/s ²
Accuracy	±0.05% of setting
Squitter	0 to 8000 Hz
Resolution	1 Hz
Accuracy	10 Hz or 2%, whichever is greater
Spectrum at ±800 KHz Offset	> 55dB below center frequency level
Reply Efficiency	0 to 100 %
Resolution	1%
Accuracy	±0.5%

Receiver

VSWR

<1.4

Max Input Power

+60 dBm

Receiver Decoding

Messages	ATCRBS Interrogation and Replies
	Mode S Interrogations and Replies
	UAT Ground and Airborne Messages [UAT Option]

Dynamic Range

1090 MHz	>40 dB
UAT	>30 dB

Channels

No. of Channels	2, Top/Bottom
-----------------	---------------

Measurement

Power	+17 to +60 dBm
Resolution	0.1 dB
Accuracy	± 0.5 dB

Receiver (continued)

Measurement (continued)	
Frequency	
Pulse Measurement Type	1090 MHz \pm 3 MHz
Resolution	1 KHz
Accuracy	\pm 50 KHz
Pulse Spacing	
Resolution	1 nS
Accuracy	\pm 10 nS
Pulse Width	
Resolution	1 nS
Accuracy	\pm 10 nS
Pulse Rise/Fall Time	
Resolution	1 nS
Accuracy	\pm 20 nS
ATCRBS Reply Delay	
Resolution	25 nS
Accuracy	\pm 20 nS
Mode S Reply Delay	
Resolution	25 nS
Accuracy	\pm 20 nS
Reply Jitter	
Resolution	25 nS
Accuracy	\pm 20 nS

Environmental

Temperature	
Full specified performance	23 °C, \pm 5 °C (73.4 °F, \pm 41 °F)
Operating	0 to +40 °C (32° to 104 °F)
Storage	0 to +71 °C (32° to 159.8 °F)
Relative Humidity	0 to 95% noncondensing

Physical Characteristics

Dimensions	10.5 in x 19 in x 24 in (26.7 cm x 48.3 cm x 60.9 cm)
Weight	41 lbs (18.6 kg) test set only 53 lbs (24.04 kg) shipping weight 89 lbs (40.37 kg) shipping weight with optional transit case

Functional Characteristics

Remote Interface
Optional Command set emulation of the SDX-2000, ATC-1400A and S-1403DL
Ethernet
GPIB
Inputs/Outputs
Suppression bus (front/back)
2 scope BNC outputs (front/back)
LAN (front/back)
USB Type B control (front)
2 USB Type A (front) for HID/flash drives
Test Set Certifications
MIL-PRF-28800F (Class 3 Device)
CE
UL/EN 61010-1
EN 61326-1



Contact Us +1 316 522 4981
AvComm.TechSales@viavisolutions.com

To reach the VIAVI office nearest you, visit
[viavisolutions.com/contact](https://www.viavisolutions.com/contact).

© 2020 VIAVI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
ATC5000NG-ss-avi-nse-ae
30186498 901 0220